

RAVENOL MARINEOIL DIESEL SHPD 20W-50

Մածուցիկություն: 20W-50

Mineral



1 l

Հոդված:

1163110-001

Հոդված:

1163110-001-01-999



4 l

Հոդված:

1163110-004

Հոդված:

1163110-004-01-999



10 l

Հոդված:

1163110-010



20 l

Հոդված:

1163110-020

Հոդված:

1163110-020-01-999



20 l, ecobox

Հոդված:

1163110-B20



60 l

Հոդված:

1163110-060

Հոդված:

1163110-060-01-999



208 l

Հոդված:

1163110-208

Հոդված:

1163110-208-01-999



1 000 l

Հոդված:

1163110-700

RAVENOL MARINEOIL DIESEL SHPD 20W-50 is a SHPD multi-range engine oil for marine diesel engines. RAVENOL MARINEOIL DIESEL SHPD 20W-50 corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions. Quality Classification: RAVENOL MARINEOIL DIESEL SHPD 20W-50 is tried and tested for aggregates specifying: Specifications: API CI-4, ACEA E7, B4 Recommendations: Steyr, Mercruiser, Yanmar Technical Characteristics: RAVENOL MARINEOIL DIESEL SHPD 20W-50 offers: an extreme high pressure absorption capacity, a very high oxidation stability, an excellent aging resistance, an excellent viscosity temperature behaviour, high safety reserves also under boundary lubrication conditions, suitability for extended oil change intervals, suitability for complicate operating conditions, a good water separation behaviour. Technical Values: Characteristics Unit Data Test according to Density at 20°C kg/m³ 881,0 EN ISO 12185 Colour blue visual Viscosity at 100°C mm²/s 18,4 DIN 51562-1 Viscosity at 40°C mm²/s 161,3 DIN 51562-1 Viscosity Index VI 128 DIN ISO 2909 Pourpoint °C -36 DIN ISO 3016 Flashpoint °C 250 DIN ISO 2592 TBN mg KOH/g 11,2 ASTM D2896 Sulphated ash %wt. 1,44 DIN 51575 All indicated data are approximate values and are subject to the commercial fluctuations.

Application Note

RAVENOL MARINEOIL DIESEL SHPD 20W-50 is tried and tested for aggregates specifying: Specifications: API CI-4, ACEA E7, B4 Recommendations: Steyr, Mercruiser, Yanmar Technical Characteristics: RAVENOL MARINEOIL DIESEL SHPD 20W-50 offers: an extreme high pressure absorption capacity, a very high oxidation stability, an excellent aging resistance, an excellent viscosity temperature behaviour, high safety reserves also under boundary lubrication conditions, suitability for extended oil change intervals, suitability for complicate operating conditions, a good water separation behaviour. Technical Values: Characteristics Unit Data Test according to Density at 20°C kg/m³ 881,0 EN ISO 12185 Colour blue visual Viscosity at 100°C mm²/s 18,4 DIN 51562-1 Viscosity at 40°C mm²/s 161,3 DIN 51562-1 Viscosity Index VI 128 DIN ISO 2909 Pourpoint °C -36 DIN ISO 3016 Flashpoint °C 250 DIN ISO 2592 TBN mg KOH/g 11,2 ASTM D2896 Sulphated ash %wt. 1,44 DIN 51575 All indicated data are approximate values and are subject to the commercial fluctuations.

Բնութագրերը

Մնուն	Իմաստը	Մուդիտ
API	CI-4	
ACEA	B4, E7	
Համապատասխանում է	Mercruiser, STEYR, Yanmar	
Հատուկ հզորություն 20°C-ի դեպքում	878 գ/սմ ³	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	18.4 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	161.3 mm ² /s	DIN 51562-1
Մածուցիկության ինդեքս VI	128	DIN ISO 2909
Բյուրեղացման ջերմաստիճան	-36 °C	DIN ISO 3016
Կառուցման ջերմաստիճան	250 °C	DIN EN ISO 2592
TBN	11.2 մգ KOH/գ	ASTM D2896
Սուլֆատային հոլմքի պարունակություն	1.2 %wt.	DIN 51575
Շարժիչի տակտայնություն	4T	

Դադարեցված փաթեթավորում

Փաթեթավորում	Հոդված	Շտրիխ կոդ
1 լ	1163110-001-06-999	
10 լ	1163110-010-01-999	