

RAVENOL Gas Engine Oil LFG 40

Yopishqoqlik: 40W

Mineral



20 L

Mahsulot kodi:
1133106-020



20 L, ecobox

Mahsulot kodi:
1133106-B20



60 L

Mahsulot kodi:
1133106-060



208 L

Mahsulot kodi:
1133106-208



1 000 L

Mahsulot kodi:
1133106-700

Xususiyatlari

Ism	Ma'nosi	Audit
Ishlab chiqaruvchi tomonidan ma'qullangan	MAN M 3271-4 (special gas), MAN M 3271-5	
Talablarga mos keladi	General Electric Jenbacher General Electric Jenbacher Type 2 (A & B) - Gas B & C, General Electric Jenbacher Type 3 (A & B) - Gas B & C, General Electric Jenbacher Type 4 (A & B) - Gas B & C, General Electric Jenbacher Type 6 (C & E) - Gas B & C	
Mos keladi	Caterpillar CG gas engines, MWM TCC gas engines	
Zichlik 20°C da	879 g/cm ³	EN ISO 12185
Rang	Jigarrang	ingl
Viskozite 100°C da	13.5 mm ² /s	DIN 51659-2
Viskozite 40°C da	129.1 mm ² /s	DIN 51659-2
Viskozite indeksi VI	100	DIN ISO 2909
Qotish harorati	-21 °C	DIN ISO 3016
Yong'in chiqish harorati	276 °C	DIN EN ISO 2592
NOACK bug'lanishi	3 %	ASTM D5800
Tavsiyalar	General Electric Jenbacher Typ 2 (A & B) - Gas B & C, General Electric Jenbacher Typ 3 (A & B) - Gas B & C, General Electric Jenbacher Typ 4 (A & B) - Gas B & C, General Electric Jenbacher Typ 6 (C & E) - Gas B & C	
Mis plastinkaga ta'sir testi, 150°C da	1b	ASTM D130
Yuqori haroratli viskozite (HTHS) 150°C da	3.91 mPa*s	ASTM D5481
Ishqoriy son	4.4 mgKOH/g	ASTM D2896