

# 4T qayiq dvigatellari uchun motor moyi - RAVENOL Outboardoil 4T 15W-40

Yopishqoqlik: 15W-40

Mineral



**1 L**

Mahsulot kodi:

**1153205-001**

Mahsulot kodi:

1153205-001-01-999

Shtrix-kod:

4014835729216



**4 L**

Mahsulot kodi:

**1153205-004**

Mahsulot kodi:

1153205-004-01-999

Shtrix-kod:

4014835729292



**5 L**

Mahsulot kodi:

**1153205-005**

Mahsulot kodi:

1153205-005-01-999

Shtrix-kod:

4014835729254



**10 L**

Mahsulot kodi:

**1153205-010**

Mahsulot kodi:

1153205-010-01-999

Shtrix-kod:

4014835729247



**20 L**

Mahsulot kodi:

**1153205-020**



**20 L, ecobox**

Mahsulot kodi:

**1153205-B20**

Mahsulot kodi:

1153205-B20-01-888

Shtrix-kod:

4014835780729



**60 L**

Mahsulot kodi:

**1153205-060**



**208 L**

Mahsulot kodi:

**1153205-208**

RAVENOL Outboardoil 4T SAE 15W-40 – mineral motor moyi bo'lib, NMMA FC-W talablari asosida in'yeksiya tizimiga ega 4 taktili tashqi qayiq dvigatellari uchun maxsus ishlab chiqilgan. Yuqori aylanish tezligi va yuklama sharoitida ham mukammal moylashni, kam kulli qo'shimchalar orqali ishqalanishga qarshi himoyani hamda korroziyadan himoyani ta'minlaydi. Ko'k rangga bo'yalgan.

NMMA FC-W sifat darajasidagi moy talab qilinadigan 4 taktili tashqi qayiq dvigatellarida qo'llaniladi, dengiz suvida ekspluatatsiya qilish uchun ham mos keladi.

**Outboardoil 4T SAE 15W-40** quyidagilarni ta'minlaydi:

- Korroziyaga qarshi optimal himoya
- Yoqilg'i (shu jumladan etilsiz benzin) bilan aralashishga yaroqlilik
- Yuqori harorat va yuqori yuklamalarda ham barqaror moyli plyonka
- Zo'r ishqalanishga qarshi xususiyatlar
- Cho'kma hosil qilmasdan to'liq yonish
- Past darajadagi kokslash
- Ishqalanishga qarshi himoya

## Xususiyatlari

| Ism                                       | Ma'nosi                                                                   | Audit           |
|-------------------------------------------|---------------------------------------------------------------------------|-----------------|
| Ishlab chiqaruvchi tomonidan ma'qullangan | NMMA FC-W, NMMA FB-83138K                                                 |                 |
| Mos keladi                                | Evinrude, Honda, Johnson, Mercury Verado, Nissan, Suzuki, Tohatsu, Yamaha |                 |
| Zichlik 20°C da                           | 864 g/cm <sup>3</sup>                                                     | EN ISO 12185    |
| Rang                                      | Ko'k                                                                      | ingl            |
| Viskozite 100°C da                        | 14.4 mm <sup>2</sup> /s                                                   | DIN 51562-1     |
| Viskozite 40°C da                         | 98.6 mm <sup>2</sup> /s                                                   | DIN 51562-1     |
| Viskozite indeksi VI                      | 150                                                                       | DIN ISO 2909    |
| Qotish harorati                           | -33 °C                                                                    | DIN ISO 3016    |
| Yong'in chiqish harorati                  | 236 °C                                                                    | DIN EN ISO 2592 |
| Ishqoriy son                              | 7.5 mgKOH/g                                                               | ASTM D2896      |
| Tavsiyalar                                | Evinrude, Honda, Johnson, Mercury Verado, Nissan, Suzuki, Tohatsu, Yamaha |                 |
| Dvigatelning taktligi                     | 4T                                                                        |                 |

## To'xtatilgan qadoqlash

| Qadoqlash | Mahsulot kodi      | Shtrix-kod                                      |
|-----------|--------------------|-------------------------------------------------|
| 1 L       | 1153205-001-01-100 | 4014835634411<br>2200000020567                  |
| 4 L       | 1153205-004-01-999 |                                                 |
| 5 L       | 1153205-005-01-100 | 4014835634459<br>2200000030597<br>2200000032478 |
| 10 L      | 1153205-010-01-999 |                                                 |
| 20 L      | 1153205-020-01-999 |                                                 |
| 60 L      | 1153205-060-01-999 |                                                 |
| 208 L     | 1153205-208-01-999 |                                                 |