

2T qor skuterlari uchun moy - RAVENOL Snowmobiles Mineral 2-Takt

Mineral



1 L

Mahsulot kodi:

1153310-001

Mahsulot kodi:

1153310-001-01-999

Shtrix-kod:

4014835729513



4 L

Mahsulot kodi:

1153310-004

Mahsulot kodi:

1153310-004-01-999

Shtrix-kod:

4014835729599



10 L

Mahsulot kodi:

1153310-010

Mahsulot kodi:

1153310-010-01-999

Shtrix-kod:

4014835729544



20 L

Mahsulot kodi:

1153310-020



20 L, ecobox

Mahsulot kodi:

1153310-B20

Mahsulot kodi:

1153310-B20-01-888

Shtrix-kod:

4014835781023



60 L

Mahsulot kodi:

1153310-060

Mahsulot kodi:

1153310-060-01-999

Shtrix-kod:

4014835729568



208 L

Mahsulot kodi:

1153310-208



1 000 L

Mahsulot kodi:

1153310-700

RAVENOL SNOWMOBILES Mineral 2-Takt – Germaniyada yuqori darajada tozalangan asosiy moy asosida ishlab chiqarilgan yuqori sifatli mineral motor moyi.

RAVENOL SNOWMOBILES Mineral 2-Takt motor moyi formulasi zamonaviy qor motosikllari dvigatellari uchun maxsus ishlab chiqilgan. Maksimal aylanish tezligida yuzaga keladigan qisqa muddatli kuchlanishlar kabi ekstremal og'ir sharoitlarda ham dvigatelni ishonchli himoya qiladi.

RAVENOL SNOWMOBILES Mineral 2-Takt mineral motor moyi ham yog'ni in'yeksiya orqali yuboradigan tizimlarda, ham oldindan aralashtirilgan tizimlarda qo'llaniladi. Moy tarkibidagi yuqori sifatli solvent past alanganish haroratini ta'minlaydi.

RAVENOL SNOWMOBILES Mineral 2-Takt benzin-moy aralashmasining oktan sonini oddiy benzin bilan solishtirganda o'zgartirmaydi. Aralashmani tayyorlashdagi odatiy nisbati 1:25 dan 1:50 gacha bo'lishi mumkin. Biroq har bir dvigatel modeli bo'yicha ishlab chiqaruvchining aralashma dozlashiga oid tavsiyalariga amal qilish zarur.

Zamonaviy qor motosikllarining ayrim modellari dvigatel ish rejimiga qarab avtomatik dozlashni amalga oshiradi.

Motor moyini tanlashda xatoga yo'l qo'ymaslik va yoqilg'i aralashmasida moy mavjudligini aniqlash uchun RAVENOL SNOWMOBILES Mineral 2-Takt mahsuloti ko'k rangga bo'yalgan.

Shuni inobatga olish lozimki, agar RAVENOL SNOWMOBILES Mineral 2-Takt in'yektorli tizimlarda qo'llanilsa, uni qo'llash harorati in'yektor nasosi tebranish harorati -20°C darajagacha cheklanadi.

Agar undan past haroratda ishlatish zarur bo'lsa, RAVENOL SNOWMOBILES Teilsynth. 2-Takt yoki RAVENOL SNOWMOBILES Vollsynth. 2-Takt sintetik moylaridan foydalanish yoki benzin bilan oldindan aralashtirish tavsiya etiladi, bunda kerakli konsentratsiyani hisobga olish lozim.

SNOWMOBILES Mineral 2-Takt quyidagilarni ta'minlaydi:

- Dvigatelning barcha moylangan qismlarida zo'r korroziyadan himoya
- Ishlatilayotgan yoqilg'i bilan tez va bir xil aralashuv
- Yuqori yuklamalarda ham barqaror moyli plyonka
- Cho'kmasiz toza yonish
- Koks hosil bo'lmasligi
- Zo'r ishqalanishga qarshi himoya

Xususiyatlari

Ism	Ma'nosi	Audit
API	TC	
JASO	FB	
Talablarga mos keladi	Arctic	
Spetsifikatsiyalarga mos keladi	ISO L-EGB	
Mos keladi	Bombardier, Kawasaki, Polaris, Ski-Doo, Suzuki, Yamaha	
Zichlik 20°C da	872 g/cm ³	EN ISO 12185
Rang	Ko'k	ingl
Viskozite 100°C da	9.7 mm ² /s	DIN 51562-1
Viskozite 40°C da	70 mm ² /s	DIN 51562-1
Viskozite indeksi VI	118	DIN ISO 2909
Qotish harorati	-24 °C	DIN ISO 3016
Yong'in chiqish harorati	100 °C	DIN EN ISO 2592
Tavsiyalar	Arctic Cat, Bombardier, Kawasaki, Polaris, Ski-Doo, Suzuki, Yamaha	
Dvigatelning taktligi	2T	

OEM analoglari

BRP

293600117, 293600118, 779119, 779123, 619590101, 779120, 1471499, 779277, 1471599, 1471599V, 1471600, 1471699, 293600004, 293600005, 413802900, 413803000, 496013300, 496013400, 496013800, 496014000, 779121, 779122

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1153310-001-01-100 1153310-001-06-999	4014835638716 2200000020765
10 L	1153310-010-01-999	
20 L	1153310-020-01-888 1153310-020-01-999	
208 L	1153310-208-01-999	