

# *Motor moyi RAVENOL Marineoil PETROL 25W-40 Synthetic*

**Yopishqoqlik: 25W-40**

Sintetik



## 1 L

Mahsulot kodi:

**1162115-001**

Mahsulot kodi:

1162115-001-01-999

Shtrix-kod:

4014835729810



## 4 L

Mahsulot kodi:

**1162115-004**

Mahsulot kodi:

1162115-004-01-999

Shtrix-kod:

4014835729896



## 10 L

Mahsulot kodi:

**1162115-010**

Mahsulot kodi:

1162115-010-01-999

Shtrix-kod:

4014835764941



## 20 L

Mahsulot kodi:

**1162115-020**



## 20 L, ecobox

Mahsulot kodi:

**1162115-B20**



## 60 L

Mahsulot kodi:

**1162115-060**



## 60 L, bosilgan barrel

Mahsulot kodi:

**1162115-D60**



## 208 L

Mahsulot kodi:

**1162115-208**

Mahsulot kodi:

1162115-208-01-999

Shtrix-kod:

4014835764989



**1 000 L**

Mahsulot kodi:

**1162115-700**

**RAVENOL MARINEOIL PETROL 25W-40 Synthetic** – sintetik asosga ega bo'lgan motor moyi bo'lib, 4 taktli osilgan qayiq dvigatellari uchun maxsus ishlab chiqilgan. Yuqori aylanish tezligi va yuklama sharoitida ham mukammal yog'lashni, past kul tarkibli qo'shimchalar tufayli eskirishdan himoyalashni va korroziyadan himoyani ta'minlaydi. Ko'k rangga bo'yagan.

4 taktli osilgan qayiq dvigatellarida qo'llaniladi, dengiz suvida ishlash sharoitida ham foydalanish mumkin.

**MARINEOIL PETROL 25W-40 SYNTHETIC** quyidagilarni ta'minlaydi:

- A'llo darajadagi tozalovchi va disperslovchi xususiyatlar
- Past bug'lanish yo'qotishlari
- A'llo darajadagi eskirishdan himoya
- Yaxshi ishga tushirish xususiyatlari
- Yog' va yoqilg'i sarfini kamaytirish

## Xususiyatlari

<i>Ism</i>	<i>Ma'nosi</i>	<i>Audit</i>
API	SL	
ACEA	A3, B4	
Talablarga mos keladi	DDC Detroit Diesel, VETUS DEUTZ, Volvo PENTA	
Mos keladi	Caterpillar, IVECO, MAN, MTU, Mercruiser, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, Yanmar	
Zichlik 20°C da	866 g/cm <sup>3</sup>	EN ISO 12185
Rang	Ko'k	ingl
Viskozite 100°C da	13.8 mm <sup>2</sup> /s	DIN 51562-1
Viskozite 40°C da	92.4 mm <sup>2</sup> /s	DIN 51562-1
Viskozite indeksi VI	152	DIN ISO 2909
Past haroratli viskozite (CCC) - 25°C da	6450 mPa*s	ASTM D5293
Qotish harorati	-36 °C	DIN ISO 3016
Yong'in chiqish harorati	215 °C	DIN EN ISO 2592
Ishqoriy son	11 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	1.3 %wt.	DIN 51575
Tavsiyalar	Caterpillar, Detroit Diesel, IVECO, MAN, MTU, Mercruiser, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar	
Dvigatelning taktiligi	4T	

## To'xtatilgan qadoqlash

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
1 L	1162115-001-06-999	
10 L	1162115-010-01-999	
20 L	1162115-020-01-999	
60 L	1162115-060-01-999	
208 L	1162115-208-01-000	4014835704282 2200000043030