

Mator moyi RAVENOL Motobike 4-T Ester 10W-50

Yopishqoqlik: 10W-50

Sintetik



1 L

Mahsulot kodi:

1171103-001

Mahsulot kodi:

1171103-001-01-999

Shtrix-kod:

4014835730816



4 L

Mahsulot kodi:

1171103-004

Mahsulot kodi:

1171103-004-01-999

Shtrix-kod:

4014835730892



10 L

Mahsulot kodi:

1171103-010

Mahsulot kodi:

1171103-010-01-999

Shtrix-kod:

401483588593



20 L

Mahsulot kodi:

1171103-020



20 L, ecobox

Mahsulot kodi:

1171103-B20



60 L

Mahsulot kodi:

1171103-060

Mahsulot kodi:

1171103-060-01-999

Shtrix-kod:

4014835730861



208 L

Mahsulot kodi:

1171103-208



1 000 L

Mahsulot kodi:

1171103-700

RAVENOL Motobike 4-T Ester SAE 10W-50 – bu 4 taktli mototsikl dvigatellari uchun maxsus ishlab chiqilgan zamonaviy sintetik motor moyidir. Yonilg'i tejamkorligini ta'minlaydi.

Mototsikl dvigatelini og'ir ekspluatatsiya sharoitlarida, jumladan uzoq muddatli yuqori aylanish tezligida ishonchli himoya qiladi. Quruq mufta va moyli vanna ichidagi muftali sport mototsikllarning to'rt taktli dvigatellari uchun maxsus ishlab chiqilgan.

RAVENOL Motobike 4-T Ester SAE 10W-50 — bu aynan motosport uchun yaratilgan yangi yuqori texnologiyali mahsulot hisoblanadi.

Qo'llanilishi:

SAE 10W-50 viskozit sinfidagi moy tavsiya etilgan barcha turdagi 4 taktli mototsikl dvigatellari uchun qo'llaniladi.

MOTOBIKE 4-T Ester SAE 10W-50 quyidagilarni ta'minlaydi:

- Dvigatelning tezkor yog'lanishini
- Past bug'lanish tezligi tufayli moy sarfining kamayishi
- Noqulay sharoitlarda ham shlam, nagar va korroziyadan himoya
- Har qanday haroratda klapanlarning funksional ishlashi
- Yonish kameralarida, piston halqalari va klapanlar zonasida nagar hosil bo'lmasligi
- Moy almashtirish oralig'i davomida o'zgarmas viskozitani, yuqori viskozit indeks bilan
- Muhrlovchi materiallarga nisbatan neytral ta'sir

Xususiyatlari

Ism	Ma'nosi	Audit
API	SN	
JASO	MA2	
Mos keladi	Aprilia, BMW, Ducati, Honda, Kawasaki, Moto-Guzzi, Suzuki, Triumph, Yamaha	
Zichlik 20°C da	855 g/cm ³	EN ISO 12185
Rang	Sariq-jigarrang	ingl
Viskozite 100°C da	17.6 mm ² /s	DIN 51562-1
Viskozite 40°C da	120.4 mm ² /s	DIN 51562-1
Viskozite indeksi VI	162	DIN ISO 2909
Past haroratli viskozite (CCC) - 25°C da	5914 mPa*s	ASTM D5293
Qotish harorati	-39 °C	DIN ISO 3016
NOACK bug'lanishi	5.2 %	ASTM D5800
Yong'in chiqish harorati	248 °C	DIN EN ISO 2592
Ishqoriy son	7.5 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	0.85 %wt.	DIN 51575
Tavsiyalar	Aprilia, BMW, Ducati, Honda, Kawasaki, Moto-Guzzi, Suzuki, Triumph, Yamaha	
Dvigatelning taktligi	4T	

OEM analoglari

BRP

779234, 779235

Yamaha

LUB10W50SS12, LUB10W50SS04

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1171103-001-01-100	4014835702219 2200000018632
20 L	1171103-020-01-999	

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
60 L	1171103-060-01-999	
208 L	1171103-208-01-999	