

Mator moyi RAVENOL Motobike V-Twin 20W-50 Fullsynth

Yopishqoqlik: 20W-50

To'liq sintetik



1 L

Mahsulot kodi:

1171105-001

Mahsulot kodi:

1171105-001-01-999

Shtrix-kod:

4014835803251



4 L

Mahsulot kodi:

1171105-004

Mahsulot kodi:

1171105-004-01-999

Shtrix-kod:

4014835803268



20 L

Mahsulot kodi:

1171105-020



20 L, ecobox

Mahsulot kodi:

1171105-B20



60 L

Mahsulot kodi:

1171105-060



208 L

Mahsulot kodi:

1171105-208



208 L, bosilgan barrel

Mahsulot kodi:

1171105-D28

RAVENOL Motobike V-Twin SAE 20W-50 Fullsynth – bu «3 in 1» to'liq sintetik moy bo'lib, dvigatel, uzatma va krank mil tizimlari uchun mo'ljallangan, ayniqsa Cruiser va Chopper turidagi mototsikllar uchun ishlab chiqilgan.

Treniya darajasini pasaytiradi va ventil hamda krank milida metall-metall ishqalanish yuzalarini himoya qiladi.

Havo bilan sovitiladigan, V shaklidagi ikki silindrli dvigatellar duch keladigan juda yuqori harorat sharoitida ham termal barqarorlik va chidamlilikni ta'minlaydi.

Qo'llanilishi:

RAVENOL Motobike V-Twin 20W-50 Fullsynth barcha SAE 20W-50 viskozit sinfidagi moy talab etiladigan V-Twin tipidagi Chopper va Cruiser mototsikl dvigatellarida qo'llash uchun mos keladi.

Cruiser va Chopper Motorräder uchun sinovdan o'tkazilgan

Motobike V-Twin 20W-50 Fullsynth. quyidagilarni ta'minlaydi:

- Stabil viskozit xususiyatlari
- Treniya darajasining kamaytirilishi
- Kesishga nisbatan yaxshi chidamlilik
- Yuqori ish haroratlarida kuchli yog' qatlamining saqlanishi
- A'lo darajadagi tozalovchi va disperslovchi xususiyatlar
- Eskirish va korroziyaga qarshi juda yaxshi himoya
- Ko'piklanishga qarshi himoya

Xususiyatlari

Ism	Ma'nosi	Audit
API	SL	
JASO	MA2	
Talablarga mos keladi	Indian , Moto , Suzuki V-Twin Motor Oil, Triumph , Victory	
Mos keladi	BMW Cruiser Motorcycles	
Zichlik 20°C da	858 g/cm ³	EN ISO 12185
Rang	Jigarrang	ingl
Viskozite 100°C da	19.8 mm ² /s	DIN 51562-1
Viskozite 40°C da	139.67 mm ² /s	DIN 51562-1
Viskozite indeksi VI	163	DIN ISO 2909
Past haroratli viskozite (CCS) - 15°C da	4473 mPa*s	ASTM D5293
Qotish harorati	-42 °C	DIN ISO 3016
Yong'in chiqish harorati	252 °C	DIN EN ISO 2592
Ishqoriy son	7.4 mgKOH/g	ASTM D2896
Tavsiyalar	BMW Cruiser Motorcycles, Harley Davidson 62600005, Harley Davidson 62600031, Honda 08C35-A251L01, Honda 08C35-A251M01, Indian Motorcycles, Moto Guzzi Motorcycles, Suzuki V-twin Motor Oil, Triumph Motorcycles, Victory Motorcycles, Yamalube LUB20W50AP12, Yamalube LUB20W50AP04	
Dvigatelning taktligi	4T	

OEM analoglari

BRP

779462

Honda

08C35A251M02, 08C35A251M01, 08C35A251L01

Yamaha

LUB20W50SS12

Yamalube

LUB20W50AP04, LUB20W50AP12, YMD650420100, YMD650420102, YMD650420103, YMD650420104, YMD650426001, YMD650426002, YMD650422081, YMD650422082, YMD650220101, YMD650220102, YMD650220103, YMD650220104, YMD650220105, YMD650226001, YMD650226002, YMD650226003, YMD650222080, YMD650220100, YMD650220402,

YMD650220403