

# Motor moyi RAVENOL Motobike V-Twin 20W-50 Mineral

Yopishqoqlik: 20W-50

Mineral

## 1 L



Mahsulot kodi:

**1173105-001**

Mahsulot kodi:

1173105-001-01-999

Shtrix-kod:

4014835839328

## 4 L



Mahsulot kodi:

**1173105-004**

Mahsulot kodi:

1173105-004-01-999

Shtrix-kod:

4014835839359

## 20 L



Mahsulot kodi:

**1173105-020**

## 20 L, ecobox

Mahsulot kodi:

**1173105-B20**

## 60 L



Mahsulot kodi:

**1173105-060**

## 208 L

Mahsulot kodi:

**1173105-208**

**RAVENOL Motobike V-Twin 20W-50 Mineral** – bu dvigatel, uzatma va krank vallari uchun mo'ljallangan "3 in 1" tipidagi mineral moydir. Ayniqsa Cruiser va Chopper turidagi mototsikllar uchun maxsus ishlab chiqilgan.

Treniya darajasini pasaytiradi va ventil hamda krank vallari zonasidagi metall-metall ishqalanish yuzalarini himoya qiladi.

Havo bilan sovitiladigan, V shaklidagi ikki silindrli dvigatellar duch keladigan juda yuqori harorat sharoitida ham mukammal barqarorlik va termal chidamlilikni ta'minlaydi.

**RAVENOL Motobike V-Twin 20W-50 Mineral** SAE 20W-50 viskozit sinfidagi moy talab qilinadigan barcha turdag'i Chopper va Cruiser mototsikllarining V-Twin tipidagi dvigatellarida qo'llash uchun mos keladi.

**Probandan o'tkazilgan: Cruiser va Chopper Motorräder uchun.**

**Motobike V-Twin 20W-50 Mineral** quyidagilarni ta'minlaydi:

- Stabil viskozit xususiyatlari
- Treniya darajasining kamaytirilishi
- Kesishga nisbatan yaxshi chidamlilik
- Yuqori harorat va katta yuklamalar sharoitida ham barqaror yog' qatlaming saqlanishi
- Eskirish va korroziyaga qarshi juda yaxshi himoya
- Ko'piklanishga qarshi himoya

## Xususiyatlari

<i>Ism</i>	<i>Ma'nosi</i>	<i>Audit</i>
API	SL	
JASO	MA2	
Talablarga mos keladi	Indian , Moto , Suzuki V-Twin Motor Oil, Triumph , Victory	
Mos keladi	BMW Cruiser Motorcycles	
Zichlik 20°C da	878 g/cm <sup>3</sup>	EN ISO 12185
Rang	Jigarrang	ingl
Viskozite 100°C da	20.4 mm <sup>2</sup> /s	DIN 51562-1
Viskozite 40°C da	173.4 mm <sup>2</sup> /s	DIN 51562-1
Viskozite indeksi VI	137	DIN ISO 2909
Past haroratli viskozite (CCS) - 15°C da	6459 mPa*s	ASTM D5293
Qotish harorati	-33 °C	DIN ISO 3016
Yong'in chiqish harorati	236 °C	DIN EN ISO 2592
Ishqoriy son	8.7 mgKOH/g	ASTM D2896
Tavsiyalar	BMW Cruiser Motorcycles, Harley Davidson 62600005, Harley Davidson 62600031, Honda 08C35-A251L01, Honda 08C35-A251M01, Indian Motorcycles, Moto Guzzi Motorcycles, Suzuki V-twin Motor Oil, Triumph Motorcycles, Victory Motorcycles, Yamalube LUB20W50AP04, Yamalube LUB20W50AP12	
Dvigatelning taktligi	4T	