

Transmissiya moyi RAVENOL GHA-F Gearbox Hydraulic Actuator

Mineral



1 L

Mahsulot kodi:

1181201-001

Mahsulot kodi:

1181201-001-01-999

Shtrix-kod:

4014835766013



20 L, ecobox

Mahsulot kodi:

1181201-B20

Elektr gidravlik transmissiyalar uchun maxsus gidravlik moy.

RAVENOL Gearbox Hydraulic Actuator GHA-F – bu sintetik va mineral komponentlar asosidagi, kul hosil qilmaydigan qo'shimchalar paketiga ega maxsus gidravlik moydir. Past haroratlarda a'lo ish xususiyatlariga ega.

RAVENOL Gearbox Hydraulic Actuator GHA-F -40°C dan +100°C gacha bo'lgan harorat oralig'ida qo'llanishi mumkin.

Peugeot/Citroen avtomobillaridagi MCP elektron boshqaruvli transmissiyalar, shuningdek FIAT/Alfa Romeo avtomobillaridagi Dualogic va Selespeed transmissiyalari uchun mo'ljallangan.

Quyidagi tizimlarda qo'llaniladi: tezlikni almashtirishning gidravlik drayverlari, servoprivodlar va robotlashtirilgan uzatmalar aktuatorlari, jumladan Peugeot EGS6 (Electronic Gearbox System), Citroen ETG6 (Efficient Tronic Gearbox), Fiat Dualogic, Alfa Romeo Selespeed.

Suzuki AMT Actuator Fluid 99000M24121-135 mahsulotiga analog hisoblanadi.

Gearbox Hydraulic Actuator GHA-F quyidagilarni ta'minlaydi:

- Oqish qobiliyatining ekstremal past haroratlarda ham saqlanishi
- Yaxshilangan viskozit va ishqalanish koeffitsienti
- Yuqori darajadagi eskirishdan himoya
- Yuqori termal barqarorlik
- Ko'piklanishga qarshi himoya
- Muhrlovchi materiallarga nisbatan neytral ta'sir

- Korroziyadan optimal himoya

Quyidagi talablarga mos keladi:

- Citroen/Peugeot 9979.A4 – MCP avtomatlashtirilgan uzatmalar uchun
- Fiat 9.55550-SA1 Nr.F005.F98
- Fiat/Alfa Romeo 15081616 CS SPEED – Dualogic va Selespeed transmissiyalari uchun
- Toyota 08886-02206 – gidropodveskalar uchun

Xususiyatlari

Ism	Ma'nosi	Audit
Talablarga mos keladi	Fiat 9.55550-SA1, Fiat F005.F98, Suzuki AMT Actuator Fluid	
Mos keladi	Fiat/Alfa Romeo 5081616 CS SPEED für Dualogic	
Zichlik 20°C da	827 g/cm ³	EN ISO 12185
Rang	Yashil	ingl
Viskozite 100°C da	6.6 mm ² /s	DIN 51562-1
Viskozite 40°C da	19.7 mm ² /s	DIN 51562-1
Viskozite indeksi VI	333	DIN ISO 2909
Qotish harorati	-54 °C	DIN ISO 3016
Yong'in chiqish harorati	164 °C	DIN EN ISO 2592
Tavsiyalar	Fiat 14621616, Fiat 9.55550-SA1, Fiat F005.F98, Fiat/Alfa Romeo 15081616 CS SPEED für Dualogic, Peugeot/Citroën 9979.A4 für MCP Automated Gearbox, Suzuki 99000M24121-135, Suzuki AMT Actuator Fluid	

OEM analoglari

Chery

QR512E4004011

Fiat

14621616

PSA Peugeot Citroen

00009979A4, 9979A4

Suzuki

99000M24121135

Toyota

0888602206