

## **RAVENOL AWD-H Fluid Haldex moyi**

*To'liq sintetik*



### **300 ml**

Mahsulot kodi:

**1211140-300**

Mahsulot kodi:

1211140-300-05-999

Shtrix-kod:

4014835855755



### **1 L**

Mahsulot kodi:

**1211140-001**

Mahsulot kodi:

1211140-001-01-999

Shtrix-kod:

4014835855786

RAVENOL AWD-H Fluid – yuqori sifatli, to'liq sintetik transmissiya moyi bo'lib, u maxsus qo'shimchalar va inhibitörler majmuasi bilan boyitilgan, quyidagilarni ta'minlaydi:

- Past haroratda a'lo darajadagi suyuqlik xususiyatlari
- Barqaror yopishqoqlik indeksi
- Oksidlanishga yuqori barqarorlik
- Eskirish, korroziya va ko'piklanishga qarshi himoya
- Doimiy ishqalanish koeffitsienti
- Yuqori issiqlik va oksidlanish barqarorligi
- Yaxshi past haroratdagi xususiyatlar
- Eng og'ir sharoitlarda ham yuqori kesish barqarorligi

Haldex muftasidagi suyuqlikni har 60.000 km da almashtirish kerak, aks holda transmissiya ishdan chiqishi mumkin.

### **RAVENOL AWD-H Fluid quyidagi original ATF moylariga muqobil hisoblanadi:**

- Land Rover LR054941
- Land Rover LR003136 (Haldex-Öl Baujahr 2011-2014)
- Opel/GM 93165387
- Opel/GM 1940057
- VOLVO 31367940
- VAG G052175A2 / G055175A2 / G060175A2

**Haldex** – bu elektron boshqaruvga ega bo'lgan mufta bo'lib, u shved kompaniyasi Haldex Traction tomonidan VAG kompaniyasining avtomobillariga o'rnatilgan avtomatik uzatma qutilari (AKPP) uchun ishlab chiqilgan. Ushbu tizim Audi, Volkswagen, Skoda, Seat hamda Volvo, Opel va Land Rover avtomobillarida qo'llaniladi.

Mufta orqa g'ildiraklararo differensial oldida o'rnatilgan bo'lib, zarurat tug'ilganda tortishni orqa g'ildiraklarga o'tkazadi. Yetakchi disklarga dvigateldan aylanish momenti keladi, passiv disklarga esa orqa o'q

## Xususiyatlari

| Ism                                                         | Ma'nosi                                                                                                                                                                                                                               | Audit           |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Talablarga mos keladi                                       | VW G 052 175, VW G 055 175, VW G 060 175, VW G 065 175 A2                                                                                                                                                                             |                 |
| Zichlik 20°C da                                             | 855 g/cm <sup>3</sup>                                                                                                                                                                                                                 | EN ISO 12185    |
| Rang                                                        | Och sariq                                                                                                                                                                                                                             | ingl            |
| Colour Code                                                 | 1                                                                                                                                                                                                                                     | DIN ISO 2049    |
| Viskozite 100°C da                                          | 5.4 mm <sup>2</sup> /s                                                                                                                                                                                                                | DIN 51562-1     |
| Viskozite 40°C da                                           | 24.5 mm <sup>2</sup> /s                                                                                                                                                                                                               | DIN 51562-1     |
| Viskozite indeksi VI                                        | 166                                                                                                                                                                                                                                   | DIN ISO 2909    |
| Brookfield usuli bo'yicha viskozite -40°C da                | 6060 mPa*s                                                                                                                                                                                                                            | ASTM D5481      |
| Qotish harorati                                             | -63 °C                                                                                                                                                                                                                                | DIN ISO 3016    |
| Yong'in chiqish harorati                                    | 192 °C                                                                                                                                                                                                                                | DIN EN ISO 2592 |
| To'rtsharli ishqalanish mashinasida kiyilish testi          | 0.58 mm                                                                                                                                                                                                                               | DIN 51350-3     |
| To'rtsharli ishqalanish mashinasida (ekstremal bosim) testi | 2000 / 2200 N                                                                                                                                                                                                                         | DIN 51350-3     |
| Ko'pik hosil bo'lishi I, 24°C da                            | 0/0 ml/ml                                                                                                                                                                                                                             | ASTM D892       |
| Ko'pik hosil bo'lishi II, 93.5°C da                         | 0/0 ml/ml                                                                                                                                                                                                                             | ASTM D892       |
| Ko'pik hosil bo'lishi III, 24°C dan 93.5°C gacha            | 0/0 ml/ml                                                                                                                                                                                                                             | ASTM D892       |
| Mis plastinkaga ta'sir testi, 150°C da                      | 1a                                                                                                                                                                                                                                    | ASTM D130       |
| Tavsiyalar                                                  | BMW 83222413513, GM 93165387, Land Rover LR 003136 (Haldex-Öl Baujahr 2011-2014), Land Rover LR054941 (Haldex-Öl Baujahr 2011-2014), Opel 1940057, VOLVO 31367940, VW G 052 175 A2, VW G 055 175 A2, VW G 060 175 A2, VW G 065 175 A2 |                 |

## OEM analoglari

### BMW

83222413513

### FEBI

101171, 101172, 101170

## **Ford**

8U7J8708687A, 1524498, 1931273, FU7J8708687AA, 8U7J8708687AA

## **General Motors**

88863350, 88863349, 93165387

## **Jaguar/Land Rover**

T4A15328

## **Land Rover**

LR003136, LR160851, 469815DE01, LR054941, SL12301

## **Motorcraft**

XL13

## **Opel**

1940057

## **Porsche**

00004330540

## **SWAG**

30101171, 30101172, 30101170

## **Volkswagen**

G055175A1

## **Volkswagen Group**

G065175A2, G052175A2, G065175, G052175S0, G060175A2, G060175, G055175A2, G055175, G055175S2, N052175Z0, G055175S0, G060175S0, N052175Y0, G052175, G052175A1

## **Volvo**

32240904, 32240905, 31367940, 31325136, 31367941, 1161641, 313679940, 30759648