

RAVENOL SSG 75W-80 transmissiya moyi

Yopishqoqlik: 75W-80

Sintetik



1 L

Mahsulot kodi:
1221100-001



4 L

Mahsulot kodi:
1221100-004



10 L

Mahsulot kodi:
1221100-010
Mahsulot kodi:
1221100-010-01-999
Shtrix-kod:
4014835733848



20 L

Mahsulot kodi:
1221100-020
Mahsulot kodi:
1221100-020-01-999
Shtrix-kod:
4014835733824



20 L, ecobox

Mahsulot kodi:
1221100-B20
Mahsulot kodi:
1221100-B20-01-888
Shtrix-kod:
4014835788121



60 L

Mahsulot kodi:
1221100-060
Mahsulot kodi:
1221100-060-01-999
Shtrix-kod:
4014835733862



60 L, bosilgan barrel

Mahsulot kodi:
1221100-D60



208 L

Mahsulot kodi:
1221100-208
Mahsulot kodi:
1221100-208-01-999
Shtrix-kod:
4014835733886



208 L, bosilgan barrel

Mahsulot kodi:
1221100-D28
Mahsulot kodi:
1221100-D28-01-888
Shtrix-kod:
4014835733800



1 000 L

Mahsulot kodi:
1221100-700

RAVENOL SSG Spec Synt LKW Getriebeoel 75W-80 – sintetik, oson oqadigan transmissiya moyi bo'lib, sintetik asos va maxsus qo'shimchalar majmuasi asosida ishlab chiqarilgan.

Yengil va yuk avtomobillari transmissiyasi va uzatma qutisining yuqori yuklama ostida ishlovchi elementlarini ishonchli himoya qiladi. To'liq sintetik baza komponenti **RAVENOL SSG Spec Synt LKW Getriebeoel 75W-80** ni nihoyatda past haroratlarda ham qo'llash imkonini beradi, shuningdek, yuqori termobarqarorligi sababli almashtirish intervalini uzaytiradi.

RAVENOL SSG Spec Synt LKW Getriebeoel 75W-80 – yuk avtomobillari, avtobuslar, qurilish texnikasining sinxronlashtirilgan uzatma qutilarida, shuningdek, intarder va retarder tizimlariga ega bo'lgan mexanizmlarda qo'llash uchun mo'ljallangan transmissiya moyidir.

U uzatmalarni qulay almashtirishni ta'minlaydi, (moyning ushbu turiga ruxsat berilgan) hollarda almashtirish oralig'ini 500 000 km gacha uzaytirish va ekspluatatsiya xarajatlarini kamaytirish imkonini beradi.

SSG Spec Synt LKW Getriebeoel SAE 75W-80 qo'llanishi quyidagilarni ta'minlaydi:

- A'lo darajadagi termobarqarorlik
- Rust, korroziya va ko'piklanishga qarshi ishonchli himoya
- Past muzlash harorati
- A'lo EP xususiyatlari
- Past haroratlarda silliq uzatma almashtirish
- Uzoq xizmat muddati
- Yoqilg'i tejamkorligi

Xususiyatlari

Ism	Ma'nosi	Audit
API	GL-4	
Ishlab chiqaruvchi tomonidan ma'qullangan	MAN 341 Type Z4, ZF TE-ML 01L, ZF TE-ML 02L, ZF TE-ML 16K	
Talablarga mos keladi	DTFR 13D120 (MB 235.29), Eaton Extended drain, MAN 341 Type E3, MAN 341 Type VR, MAN 341 Type Z5, Voith Type C, Volvo 97305, Volvo 97307, ZF TE-ML 01E, ZF TE-ML 02E, ZF TE-ML 16P	
Spetsifikatsiyalarga mos keladi	MIL-L-2105	
Mos keladi	IVECO, Renault	
Zichlik 20°C da	855 g/cm ³	EN ISO 12185
Rang	Qizil	ingl
Viskozite 100°C da	9.29 mm ² /s	DIN 51562-1
Viskozite 40°C da	51.97 mm ² /s	DIN 51562-1
Viskozite indeksi VI	163	DIN ISO 2909
Brookfield usuli bo'yicha viskozite -40°C da	38.800 mPa*s	ASTM D2983
Qotish harorati	-42 °C	DIN ISO 3016
Yong'in chiqish harorati	238 °C	DIN EN ISO 2592
Misga nisbatan korroziya testi, 121°C / 3 soat	1b	ASTM D130
Tavsiyalar	DAF/VOLVO 97305, DAF/VOLVO 97307, DTFR 13D120 (MB 235.29), Eaton (Extended drain), IVECO, MAN 341 E3, MAN 341 VR, MAN 341 Z5, Renault, VOLVO 97317, Voith Typ C, ZF TE-ML 01E, ZF TE-ML 02E, ZF TE-ML 16P	

OEM analoglari

Alpine

0101683, 0101684, 0101685

DAF

1659981, 09226BN, 1659989, 1659982, 1659982G, 09052IT, 09225RU, 09069RU, 09069EU, 1659988, 1659988G, 09069IT

FEBI

170126, 170127, 170134

Hyundai Motor
0450000440

MAN
09110700672

Pentosin
1027107

Porsche
00004330300

Volvo
85123561, 85113903, VPO120549, MVBVISHIFT75W80JUG, VPO120548, MVBVISHIFT75W80PAIL, 85136277, 85108170, 85123562, 85113904, 85136278, 85108171, 1161950

ZF
0671090386, S0671090384, S0671090386, 671090386, 0671090383, 671090383, S0671090383, 671090384, 0671090384, 0671090385, S0671090385, 671090385, S671090385

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1221100-001-01-999	4014835646421
	1221100-001-06-999	
4 L	1221100-004-01-999	
10 L	1221100-010-01-999	
20 L	1221100-020-01-000	
20 L, ecobox	1221100-B20-01-888	
60 L	1221100-060-01-999	
208 L	1221100-208-01-888	
	1221100-208-01-999	
208 L	1221100-208-01-000	4014835646483
	1221100-208-01-888	