

# RAVENOL STOU 10W-30

**Yopishqoqlik: 10W-30**



## 5 L

Mahsulot kodi:  
**1310100-005**



## 20 L

Mahsulot kodi:  
**1310100-020**  
Mahsulot kodi:  
1310100-020-01-999  
Shtrix-kod:  
4014835739529



## 20 L, ecobox

Mahsulot kodi:  
**1310100-B20**



## 60 L

Mahsulot kodi:  
**1310100-060**  
Mahsulot kodi:  
1310100-060-01-999  
Shtrix-kod:  
4014835739567



## 208 L

Mahsulot kodi:  
**1310100-208**  
Mahsulot kodi:  
1310100-208-01-999  
Shtrix-kod:  
4014835739581



## 1 000 L

Mahsulot kodi:  
**1310100-700**

## Xususiyatlari

| Ism                      | Ma'nosi                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Audit           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| API                      | CG-4, GL-4, SF                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                 |
| ACEA                     | E3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                 |
| Talablarga mos keladi    | Allison C-4, Caterpillar TO-2, DTFR 15B110 (MB 228.3), Ford ESN-M2C 159-B, ISO VG 68 HVLP, John Deere J27, Kompessorenl: Holman Compair Kompessor, MAN 270, MB 227.1, MB 228.1, MB 228.3, MIL-L-2104 D, Massey Ferguson CMS M1139, Massey Ferguson CMS M1144, Massey Ferguson CMS M1145, New Holland ESN-M2C 159-B, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06D, ZF TE-ML 07B                                                                                                            |                 |
| Mos keladi               | Atlas Copco Kompessor                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                 |
| Zichlik 20°C da          | 867 g/cm <sup>3</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | EN ISO 12185    |
| Rang                     | Sariq-jigarrang                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | ingl            |
| Viskozite 100°C da       | 11.7 mm <sup>2</sup> /s                                                                                                                                                                                                                                                                                                                                                                                                                                                               | DIN 51562-1     |
| Viskozite 40°C da        | 74.7 mm <sup>2</sup> /s                                                                                                                                                                                                                                                                                                                                                                                                                                                               | DIN 51562-1     |
| Viskozite indeksi VI     | 151                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | DIN ISO 2909    |
| Qotish harorati          | -36 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | DIN ISO 3016    |
| Yong'in chiqish harorati | 226 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | DIN EN ISO 2592 |
| Ishqoriy son             | 12.4 mgKOH/g                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ASTM D2896      |
| Sulfatli kul miqdori     | 1.58 %wt.                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | DIN 51575       |
| Tavsiyalar               | ACEA E3, API CG-4/SF, API GL-4, Allison C4, Atlas Copco Kompessor, Caterpillar TO-2, DTFR 15B110 (MB 228.3), Getriebeöl: SAE 80W, Hydrauliköl: HVLP ISO VG 68, Kompessorenl: Holman Compair Kompessor, MAN 270, MB 227.1, MB 228.1, MB 228.3, MIL-L-2104 D, Massey Ferguson M1139, Massey Ferguson M1144, Massey Ferguson M1145, Motorenöl: SAE 10W-30, New Holland / Ford ESN-M2C-15- 9B, Spezialtraktorenöl: John Deere J27, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06D, ZF TE-ML 07B |                 |

## OEM analoglari

### Isuzu

1884057500, 1884057520, 985531930A, 1884057720

To'xtatilgan qadoqlash

| Qadoqlash | Mahsulot kodi      | Shtrix-kod                     |
|-----------|--------------------|--------------------------------|
| 208 L     | 1310100-208-01-999 |                                |
| 208 L     | 1310100-208-01-000 | 4014835636484<br>2200000046215 |