

RAVENOL Agrar Synto 5W-30

Yopishqoqlik: 5W-30

Sintetik



10 L

Mahsulot kodi:
1310250-010



20 L

Mahsulot kodi:
1310250-020
Mahsulot kodi:
1310250-020-01-999
Shtrix-kod:
4014835906532



60 L

Mahsulot kodi:
1310250-060



208 L

Mahsulot kodi:
1310250-208



1 000 L

Mahsulot kodi:
1310250-700



20 L, ecobox

Mahsulot kodi:
1310250-B20

Xususiyatlari

Ism	Ma'nosi	Audit
API	CK-4, SN	
ACEA	E11, E6, E7, E8, E9	
JASO	DH-2	
Talablarga mos keladi	Cummins CES 20076, Cummins CES 20077, Cummins CES 20081, Cummins CES 20086, DAF Extended drain, DTFR 15C100 (MB 228.31), DTFR 15C110, DTFR 15C120, Deutz DQC IV-10 LA, MAN M 3277, MAN M 3477, MAN M 3677, MB 226.9, MB 228.51, MTU Type 3.1, Mack EO-O Premium Plus, Renault RLD-3, Renault RXD, Scania LDF, Scania LDF-4, Volvo VDS-4	
Zichlik 20°C da	849 g/cm ³	EN ISO 12185
Rang	Jigarrang	ingl
Viskozite 100°C da	12.15 mm ² /s	DIN 51562-1
Viskozite 40°C da	70.8 mm ² /s	DIN 51562-1
Viskozite indeksi VI	170	DIN ISO 2909
Yuqori haroratli viskozite (HTHS) 150°C da	3.7 mPa*s	ASTM D5481
Past haroratli viskozite (CCS) - 35°C da	5530 mPa*s	ASTM D5293
Past haroratda nasoslanish viskozitesi (MRV) -40°C da	22.500 mPa*s	ASTM D4684
Qotish harorati	-42 °C	DIN ISO 3016
NOACK bug'lanishi	9.1 %	ASTM D5800
Yong'in chiqish harorati	228 °C	DIN EN ISO 2592
Ishqoriy son	10.8 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	0.96 %wt.	DIN 51575
Tavsiyalar	Cummins CES 20076, Cummins CES 20077, Cummins CES 20081, Cummins CES 20086, DAF Extended drain, DTFR 15C100 (MB 228.31), DTFR 15C110, DTFR 15C120, Deutz DQC IV-10 LA, JASO DH-2, MAN M 3277, MAN M 3477, MAN M 3677, MB 226.9, MB 228.51, MTU Typ 3.1, Mack EO-O PP (Premium Plus), Renault RXD, Renault VI RLD-3, Scania LDF, Scania LDF-4, VOLVO VDS-4	