

RAVENOL Vakuumpumpenoil ISO VG 68 vakuum moyi

Yopishqoqlik: 68

Mineral



1 L

Mahsulot kodi:
1330706-001



5 L

Mahsulot kodi:
1330706-005



20 L

Mahsulot kodi:
1330706-020
Mahsulot kodi:
1330706-020-01-999
Shtrix-kod:
4014835758728



20 L, ecobox

Mahsulot kodi:
1330706-B20



60 L

Mahsulot kodi:
1330706-060
Mahsulot kodi:
1330706-060-01-999
Shtrix-kod:
4014835758766



208 L

Mahsulot kodi:
1330706-208
Mahsulot kodi:
1330706-208-01-999

RAVENOL Vakuumpumpenoil ISO VG 68 — bu yuqori unumdorlikka va tegishli sohalarda keng qo'llanilish imkoniyatiga ega optimal legirlangan mineral vakuum moyidir.

U yaxshi yopishqoqlik-harorat ko'rsatkichlari, qarishga nisbatan yuqori chidamlilik va ishonchli korroziyadan himoya bilan ajralib turadi. Maxsus tanlangan qo'shimchalar paketi og'ir yuklama ostida ham mukammal ishqalanishga qarshi himoyani ta'minlaydi. Muhrlovchi materiallarga nisbatan neytral hisoblanadi.

RAVENOL Vakuumpumpenoil ISO VG 68 vakuum nasoslarini (plastinkali nasoslar, diffuzion nasoslar, turbonasoslar) moylash uchun qo'llaniladi, bunda mineral moydan foydalanish talab etiladi, shuningdek, karterni moylash uchun ham ishlatiladi.

Vakuumpumpenoil ISO VG 68 qo'llanilishi quyidagilarni ta'minlaydi:

- Yuqori darajadagi ish samaradorligi
- A'lo darajadagi yopishqoqlik-harorat xususiyatlari
- Zo'r darajadagi ishqalanishga qarshi himoya
- Korroziyaga qarshi mukammal himoya
- Oksidlanishga nisbatan yuqori chidamlilik
- A'lo darajadagi demulgatsion xususiyatlar
- Ko'piklanishni sezilarli darajada kamaytiradigan a'lo darajadagi demulgatsion xususiyatlar
- Muhrlovchi materiallarga nisbatan neytral ta'sir
- Past qotish harorati

Xususiyatlari

<i>Ism</i>	<i>Ma'nosi</i>	<i>Audit</i>
Talablarga mos keladi	AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump	
Spetsifikatsiyalarga mos keladi	DIN 51506 VC, DIN 51524-2	
Zichlik 20°C da	866 g/cm ³	EN ISO 12185
Rang	Och sariq	ingl
Viskozite 100°C da	9 mm ² /s	DIN 51562-1
Viskozite 40°C da	68 mm ² /s	DIN 51562-1
Viskozite indeksi VI	106	DIN ISO 2909
Qotish harorati	-27 °C	DIN ISO 3016
Yong'in chiqish harorati	256 °C	DIN EN ISO 2592
Tavsiyalar	AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump	

To'xtatilgan qadoqlash

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
5 L	1330706-005-01-999	