

# Vakuum moyi RAVENOL Vakuumpumpenoil ISO VG 100

**Yopishqoqlik: 100****Mineral****5 L**Mahsulot kodi:  
**1330707-005****20 L**Mahsulot kodi:  
**1330707-020**  
Mahsulot kodi:  
1330707-020-01-999  
Shtrix-kod:  
4014835758827**20 L, ecobox**Mahsulot kodi:  
**1330707-B20****60 L**Mahsulot kodi:  
**1330707-060****208 L**Mahsulot kodi:  
**1330707-208**  
Mahsulot kodi:  
1330707-208-01-999  
Shtrix-kod:  
4014835758889

**RAVENOL Vakuumpumpenoil ISO VG 100** — bu yuqori unumdorlikka va tegishli sohalarda keng qo'llanilish imkoniyatiga ega optimal legirlangan mineral vakuum moyidir.

U yaxshi yopishqoqlik-harorat ko'rsatkichlari, qarishga nisbatan yuqori chidamlilik va ishonchli korroziyadan himoya bilan ajralib turadi. Maxsus tanlangan qo'shimchalar paketi og'ir yuklama ostida ham mukammal ishqalanishga qarshi himoyani ta'minlaydi. Muhrlovchi materiallarga nisbatan neytral hisoblanadi.

U vakuum nasoslarini (plastinkali nasoslar, diffuzion nasoslar, turbonasoslar) moylash uchun qo'llaniladi, bunda mineral moydan foydalanish talab etiladi, shuningdek, karterni moylashda ham ishlatiladi.

**Vakuumpumpenoil ISO VG 100** qo'llanilishi quyidagilarni ta'minlaydi:

- Yuqori darajadagi ish samaradorligi
- A'lo darajadagi yopishqoqlik-harorat xususiyatlari
- Zo'r darajadagi ishqalanishga qarshi himoya
- Korroziyaga qarshi mukammal himoya
- Oksidlanishga nisbatan yuqori chidamlilik
- A'lo darajadagi demulgatsion xususiyatlar
- Ko'piklanishni sezilarli darajada kamaytiradigan a'lo darajadagi demulgatsion xususiyatlar
- Muhrlovchi materiallarga nisbatan neytral ta'sir
- Past qotish harorati

## Xususiyatlari

<i>Ism</i>	<i>Ma'nosi</i>	<i>Audit</i>
Talablarga mos keladi	AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump	
Spetsifikatsiyalarga mos keladi	DIN 51506 VC, DIN 51524-2, ISO 6743-3 DVA, ISO 6743-3 DVC	
Zichlik 20°C da	875 g/cm <sup>3</sup>	EN ISO 12185
Rang	Sariq	ingl
Viskozite 100°C da	11.2 mm <sup>2</sup> /s	DIN 51562-1
Viskozite 40°C da	100.2 mm <sup>2</sup> /s	DIN 51562-1
Viskozite indeksi VI	98	DIN ISO 2909
Qotish harorati	-21 °C	DIN ISO 3016
Yong'in chiqish harorati	264 °C	DIN EN ISO 2592
Tavsiyalar	AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump	

## To'xtatilgan qadoqlash

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
5 L	1330707-005-01-999	
60 L	1330707-060-01-999	