

RAVENOL Turbo Oil T32 turbina moyi

Yopishqoqlik: 32W

Mineral



20 L

Mahsulot kodi:

1331114-020

Mahsulot kodi:

1331114-020-01-999



60 L

Mahsulot kodi:

1331114-060

Mahsulot kodi:

1331114-060-01-999



208 L

Mahsulot kodi:

1331114-208

Mahsulot kodi:

1331114-208-01-999



1 000 L

Mahsulot kodi:

1331114-700

Xususiyatlari

Ism	Ma'nosi	Audit
Ishlab chiqaruvchi tomonidan ma'qullangan	Siemens TLV 9013 04, Siemens TLV 9013 05	
Talablarga mos keladi	Alstom HTGD 90117 V0001 S, BS 489, Brown Boveri HTGD 90117, CEGB 207001, General Electric GEK 32568 A, General Electric GEK 32568 C, MIL-L-17672 D, U.S. Steel 120, Westinghouse Turbine Oil Spec.	
Spetsifikatsiyalarga mos keladi	DIN 51515-1 L-TD, DIN 51515-2 L-TG	
Zichlik 20°C da	849 g/cm ³	EN ISO 12185
Rang	L1.5	DIN ISO 2049
Viskozite 100°C da	5.8 mm ² /s	DIN 51562-1
Viskozite 40°C da	32.1 mm ² /s	DIN 51562-1
Viskozite indeksi VI	122	DIN ISO 2909
Qotish harorati	-12 °C	DIN ISO 3016
Yong'in chiqish harorati	232 °C	DIN EN ISO 2592
Suv miqdori	0.01 %	DIN 51777-1
FZG yuklama bosqichi Pass	10	DIN ISO 14635-1
Havoni ajratish qobiliyati (50°C da)	3	DIN ISO 9120
Mis plastinkaga ta'sir testi	pass	DIN EN ISO 2160
25°C da 600 soniyadan so'ng qolgan ko'pik hajmi	0 ml	ISO 6247
Tozalik darajasi	19/16/13	ISO 4406
25°C da ko'pikning buzilish vaqti	245 s	ISO 6247
25°C da ko'pik hajmi	60 ml	ISO 6247
Tavsiyalar	Alstom HTGD 90117 V0001 S, British Standard BS 489, Brown Boveri HTGD 90117, CEGB Standard 207001, General Electric GEK 32568 A, General Electric GEK 32568 C, MIL-L-17672 D, U.S.Steel 120, Westinghouse Electric Corp. Turbine Oil Spec.	
Suv ajralishi	35 s	DIN 51589-1
Neytrallash raqami	0.06 mg KOH/g	DIN 51558-1