

Suyuq surtma RAVENOL Super EP-Langzeitfett

Mineral



1 kg

Mahsulot kodi:

1340104-001

Mahsulot kodi:

1340104-001-03-000

Shtrix-kod:

4014835200418



5 kg

Mahsulot kodi:

1340104-005

Mahsulot kodi:

1340104-005-03-000

Shtrix-kod:

4014835200456



10 kg

Mahsulot kodi:

1340104-010

Mahsulot kodi:

1340104-010-03-000

Shtrix-kod:

4014835200463



15 kg

Mahsulot kodi:

1340104-015

Mahsulot kodi:

1340104-015-03-000

Shtrix-kod:

4014835200432



25 kg

Mahsulot kodi:

1340104-025

Mahsulot kodi:

1340104-025-03-000

Shtrix-kod:

4014835200425



100 g

Mahsulot kodi:

1340104-100

Mahsulot kodi:

1340104-100-04-999

Shtrix-kod:

4014835844513



180 kg

Mahsulot kodi:

1340104-180

Mahsulot kodi:

1340104-180-03-000

Shtrix-kod:

4014835200708



200 g

Mahsulot kodi:

1340104-200



400 g

Mahsulot kodi:

1340104-400

Mahsulot kodi:

1340104-400-04-999

Shtrix-kod:

4014835768345

RAVENOL Super EP-Langzeitfett — bu mineral asosli avtomobil surkovchi moy bo'lib, litiyli sovun bilan qotirilgan va tarkibida antioksidant, korroziyaga qarshi hamda EP qo'shimchalar mavjud. Bu qo'shimchalar moylanadigan qismlarning xizmat muddatini uzaytiradi va aşinani kamaytiradi.

U og'ir yuklamali aylanuvchi va sirpanma podshipniklarini moylash uchun mo'ljallangan, shu jumladan yuqori namlik, vibratsiya va zarbali yuklama sharoitida ham. Shuningdek, shassi, g'ildirak podshipniklari, avtomobil, qurilish, sanoat va qishloq xo'jaligi texnikasidagi kardanning sharnirlarini moylashda ham qo'llanilishi mumkin. Qo'llaniladigan harorat diapazoni: -30°C dan +130°C gacha (qisqa muddatli yuklama ostida +150°C gacha). NLGI klassi 2. Almashtirish oralig'i uzaytirilgan.

Super EP-Langzeitfett qo'llanilishi quyidagilarni ta'minlaydi:

- Turli texnika turlari uchun universal qo'llanilish imkoniyati
- A'lo EP xususiyatlari va aşinaga qarshi himoya
- Nam muhitda ham oksidlanish va korroziyaga qarshi samarali himoya
- Juda yaxshi mexanik barqarorlik
- Zo'r darajadagi suvga chidamlilik
- Uzoq xizmat muddati va natijada almashtirish intervallarining kengayishi
- Qarishga nisbatan mukammal chidamlilik
- Past haroratlarda ham yaxshi nasoslanish xususiyati

Xususiyatlari

Ism	Ma'nosi	Audit
Ishlab chiqaruvchi tomonidan ma'qullangan	LOVAT LOV-204	
Spetsifikatsiyalarga mos keladi	DIN 51502 KP2K-30, ISO I6743-9: ISO-L-XCCFB2	
Rang	Jigarrang	ingl
Qovushqoqlashtiruvchi modda	Litiyev sovun asosida	DIN 51757
NLGI-Class	2	DIN 51818
Mahsulotlar tasnifi	KP2K-30	DIN 51502
Ish harorati	-30 / +120 °C	DIN 51825
Ish harorati (qisqa muddatli)	130 °C	DIN 51757
Penetratsiya, 60 aylanish	265-295	ISO 2137
Korroziyadan himoya testi, namlik kamerasi	1	DIN 51802
Tomchilash harorati	180 °C	DIN ISO 2176
Misga korroziya testi, 120°C/24 soat	1	DIN 51811
Suv o'tkazmaslik (3 soat/90°C)	1-90 °C	DIN 51807-1
VKA payvandlash yuklamasi	2400 - 2600 N	DIN 51350-4
Kinematik viskozite 40°C da	130 mm²/s	DIN 51562-1

OEM analoglari

Alpine

0101025, 0101021, 0101022, 0101023, 0101024, 0101026

Toyota

PZ4550C0D090, 0888700101, 0888700401, 0888783010

Volvo

1161748

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
10 kg	1340104-010-03-111	2200000013989
180 kg	1340104-180-03-000	

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
180 kg	1340104-180-03-111	2200000009166 2200000045041
400 g	1340104-400-04-000	4014835200449 2200000032300